

# ORIKON-TECH, s.r.o.

SPECIAL SEWING THREADS

## SEWING THREAD REZITERM ST-333 (OVERLOCK)

### technical specification

**REZITERM ST-333** is PTFE coated sewing thread based on the continuous „E-Glass“ filament yarns. PTFE coating encapsulates the thread, enhancing chemical resistance and sewing capabilities.

Base filament yarn	EC6 33 tex
Fabric conditioner (optional)	DC200/200 silicone oil
Structure	33tex X 3
Nominal twist [1/m]	430Z (11TPI)
Nominal diameter [mm]	0.32
Minimal tensile strenght [N]	38
Tensibility [%]	1.2
Temperature resistance – continuous [°C]	400
Temperature resistance – momentary [°C]	450
Coating type	PTFE , sintered
Minimal PTFE coating [% of weight]	18

Packaging : 145mm cone bobbins (2000m), 35 bobbins in box

**ORIKON-TECH, s.r.o.**  
HQ: Na Dlouhých 67, 312 00, Plzeň  
KvK no.: 29118051, VAT no.: CZ29118051  
e-mail: [info@orikon.cz](mailto:info@orikon.cz), [www.orikon.cz](http://www.orikon.cz)  
tel.: +420 603 437 611

Plant: Malá Veleň 89  
405 02 Děčín